



中国认可
国际互认
检测
TESTING
CNAS L4840

Test Report

Sample Name:

Gearbox

Client:

Zhejiang Chengda Valve Drive Co., Ltd

Manufacturer:

Zhejiang Chengda Valve Drive Co., Ltd

Test Type:

Entrusted Inspection

Wuxi RELLAB Testing Services Co., Ltd.



Test Report

Client/Add: Zhejiang Chengda Valve Drive Co.,Ltd
122 Dongyang Road, Oubei Heyi Industrial Zone, Yongjia County, Wenzhou City,
Zhejiang Province

Receipt Date: Dec. 29,2023

Test Periods: Jan. 03,2024~Jan. 05,2024

The following sample information were submitted by client:

Sample Name: Gearbox

Sample Quantity: 1 pc

Type/Model: QWS05

Other Sample Information: /

Manufacturer/Add: Zhejiang Chengda Valve Drive Co.,Ltd
122 Dongyang Road, Oubei Heyi Industrial Zone, Yongjia County, Wenzhou City,
Zhejiang Province

Conclusion:

Test Sample	Test Item	Judge
Gearbox	Dust proof test (IP6X)	P
	Waterproof test (IPX8)	P

Conformity judge: P-Pass F-Fail N/A-Not Applicable



Signed Date: Jan. 15,2024

Edited by

Yu Qiu

Yu Qiu

Jan. 15,2024

Reviewed by

Will Qin

Will Qin

Jan. 15,2024

Approved by

Dawei Zhang

Dawei Zhang

Jan. 15,2024

Test Report

I Test Item: Dust proof test (IP6X)、 Waterproof test (IPX8)

1 Test Ambient:

Temperature: (23~25)°C Relative humidity: (49~54) %RH Air Pressure: 101kPa

Detection of address: Add 2

2 Test Instruments:

Table 1 Test Instruments

No.	Name	Equipment No.	Period of measurement
1	Sand and dust test chamber	WXR002	Mar. 01,2024
2	Pressure immersion test device	WXR157	Mar. 01,2024

3 Test Process:

Test Method: GB/T 4208-2017 13.4,14.2.8

Table 2 Test Conditions

Test Items	Test Conditions	
Dust proof test (IP6X)	The test should be carried out in a dustproof box. The talc powder should be filtered through metal square holes. The wire diameter is 50µm and the screen size is 75µm. The amount of talc powder is 2kg according to the volume of each cubic meter test box, and the number of uses does not exceed 20 times. During the test, the tested shell should be put into the test box according to the normal working position and connected with the vacuum pump, and the pressure should not exceed 2kPa (20 mbar). Under normal circumstances, the hole is still open during the test, and the test lasts for 2h.	
Waterproof test (IPX8)	Depth of immersion	1.2m
	Test time	1h

4 Test Result:

Judgement basis: GB/T 4208-2017 6,13.6.2

Table 3 Test Results

Test Items	Sample number	Technical requirements	Test Results	Judge
Dust proof test (IP6X)	23122902302	There was no significant dust deposition in the shell after the test	After the test, the sample did not enter the dust phenomenon.	Pass
Waterproof test (IPX8)		After continuous diving, the water intake of the outer shell will not reach harmful effects	After the test, the sample has no water inlet phenomenon.	Pass



Fig. 1. The representative appearance photo of the sample before the test




Fig. 2. The representative appearance photos of the sample during the test



Fig. 3. The representative appearance photos of the sample after the test

---The End---

Attention

- 1 The report is invalid without the company's special inspection and testing seal.
- 2 This report is not allowed to be partially copied without our company's permission.
- 3 The copied report is invalid without the company's special seal for inspection and testing.
- 4 The report is invalid without all signatures of the persons who prepared, supervised and approved.
- 5 The report is invalid with self-modification, addition and deletion.
- 6 The company is only responsible for the test results of the tested samples.
- 7 The company is responsible for all the information in the test report, except the information (including data) provided by the entrusting party. When the information (including data) provided by the entrusting party may affect the validity of the test results of the company, the company hereby makes a disclaimer.
- 8 If there is any objection to the report, client shall lodge a complaint with the company on the 15 working days from the date of receipt of the report. No late application will be accepted.
- 9 The report can be used as scientific research, teaching, internal quality control and other activities without CMA marking, and has no social proof function.
- 10 Samples submitted for inspection must be received within two months after receiving this test report, and the overdue samples shall be handled by our company, except for the special provisions of laws and regulations and technical document.

